PRINT FILE SPECIFICATIONS

PRINT MAGAZINE

2/1 SPREAD
420 mm x 250 mm (+5mm bleed)

1/1 PAGE
210 x 250 mm
(+5mm bleed)

For a customized proposal please contact:

sales@boardroom.global
+32 2 743 47 20

DIGITAL SPECIFICATIONS (PDF/X-1A FILES REQUIRED)

- Files have to be sent in 300dpi pdfs
- No cutting or print marks allowed
- All furnished PDF files should comply with PDF X-1a specifications.
- All high-resolution images and fonts must be included (linked and updated) when the PDF/X1a file is saved.
- Images must be SWOP (CMYK or Grayscale), TIFF or EPS between 200 and 400 dpi.
- Do not nest EPS file into other EPS files. Do not embed ICC Profiles within images.
- Fonts can be Type 1, Open type, or TrueType fonts. Multiple Master fonts are not recommended.
- Do not submit CT/LW, TIFF-IT, or DCS files embedded in a PDF "wrapper" (PDF to go).
- Ensure that all image, art, tint and type elements are set to knock out or overprint as desired; do not use registration color or 4/c black for text.
- The ad should be right-reading, in portrait mode, at 100% size, and no rotations.
- Exporting a PDF from Photoshop is not recommended. Composite fonts (also known as CID or "Identity-H" fonts) have a risk of not imaging correctly.